

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1. (original) A method for encoding digital data comprising:  
partitioning the digital data into a plurality of blocks;  
extracting signature information from a first one of said blocks;  
selecting a second one of said blocks as a masking block;  
embedding said signature information of said first block in said masking block.
2. (original) The method of claim 1 further comprising repeating said extracting, selecting and embedding steps for each of said plurality of blocks.
3. (original) The method of claim 1 further comprising repeating said extracting, selecting and embedding steps for each of said plurality of blocks such that each of said plurality of blocks serves as a masking block for one and only one other block.
4. (original) The method of claim 1 wherein said selecting step is performed by scanning said plurality of blocks using a predefined scanning pattern.

5. (original) The method of claim 4 further comprising expressing said plurality of blocks in a predetermined column and row format and wherein said scanning pattern traverses a diagonal zig-zag pattern across said column and row format.

6. (original) The method of claim 1 wherein said extracted signature information is content-associative signature information.

7. (original) The method of claim 1 wherein said extracted signature information is generated by expressing said data in the frequency domain having corresponding frequency coefficients and by using a selected portion of said frequency coefficients to generate said signature information.

8. (original) The method of claim 1 wherein said embedding step is performed so as to minimize the perceptibility of said signature information within said masking block.

9. (original) The method of claim 1 wherein said embedding step is performed using a data hiding technique in which the least significant bits of the masking block are altered based on the signature information.

10. (original) The method of claim 1 wherein said step of selecting a masking block is performed by expressing said plurality of blocks geometrically and by maximizing the distance between said first and second blocks.

11. (original) The method of claim 1 wherein said step of selecting a masking block is performed using a circular selection strategy whereby said first block both provides signature information to and receives signature information from a linked list of blocks containing at least one third block.

12. (original) The method of claim 1 wherein said step of selecting a masking block is performed using a random selection strategy whereby said first block and said second block are selected by a random shuffle algorithm.

13. (original) The method of claim 1 wherein said embedding step is performed using a nonlinear embedding strategy whereby the amount of signature information stored in a given block is controlled based on the data content of that block.

14. (original) The method of claim 1 wherein said embedding step is performed using a nonlinear embedding strategy whereby said plurality of blocks are classified according to a predetermined set of block types and wherein the amount of signature information stored in a given block is controlled based on the given block's block type.

15. (previously presented) A method of performing data reconstruction, comprising:

accessing processor memory containing digital data that has been encoded by:

- (a) partitioning the digital data into a plurality of blocks;
- (b) extracting signature information from a first one of said blocks;
- (c) selecting a second one of said blocks as a masking block; and
- (d) embedding said signature information of said first block in said

masking block;

examining said one of said blocks to detect if an error condition exists in that block;

upon detection of an error condition, accessing said second block to retrieve the signature information of said first block; and

using said retrieved signature information to make repairs to said first block.

16. (original) The method of claim 15 further comprising identifying additional blocks in a neighborhood associated with said first block and using said additional blocks along with said retrieved signature information to make repairs to said first block.

17. (original) The method of claim 16 wherein a multidirectional interpolation process is performed on said additional blocks to make repairs to said first block.

18. (previously presented) The method of claim 1 further comprising:  
identifying additional blocks in a neighborhood associated with said first block;  
extracting edge signature information from said additional blocks; and  
using said extracted edge information in generating said signature information.

19. (cancelled)

20. (cancelled)

21. (cancelled)

22. (cancelled)

23. (cancelled)

24. (previously presented) A system for performing data reconstruction,  
comprising:

processor memory containing digital data that has been encoded by:

- (a) partitioning the digital data into a plurality of blocks;
- (b) extracting signature information from a first one of said blocks;
- (c) selecting a second one of said blocks as a masking block; and
- (d) embedding said signature information of said first block in said

masking block;

a processor for examining said one of said blocks to detect if an error condition exists in that block;

said processor having an algorithm that causes said processor to access said second block to retrieve the signature information of said first block and to make repairs to said first block using said retrieved signature information.

25. (cancelled)